



MODEL 1100

NEW
CONSTRUCTION
SLIDING
PATIO DOOR

EXPERTLY CRAFTED FOR ENDURING
BEAUTY AND STRENGTH



MODEL 1100

SLIDING PATIO DOOR

The Gentek 1100 new construction sliding patio door merges exceptional quality and style with advanced energy-saving technology. The heavy-duty design, beautiful aesthetics and easy-care features make it an excellent choice for residential, multi-family or light commercial applications.



for casual elegance.

SUPERB FORM AND FUNCTIONALITY

- Fully fusion-welded sash and frame with integral nail flange increase structural integrity and strength
- Fortified with steel-reinforced vertical sash components for added rigidity and durability
- · Adjustable tandem rollers ensure smooth gliding of the door panel
- Extruded aluminum roller track helps prevent corrosion
- Screen features four-point roller adjustment for easy operation
- Unit is fully field-reversible²
- Available in a 2-lite style in 5', 6' and 8' widths, and a 3-lite style in a 9' width
- Integral transom in 10", 12" or 14" heights is offered for all models

ADDITIONAL FEATURES

- Insulating double barrier-fin weatherstripping at the sash sides improves energy efficiency and helps block noise and air infiltration
- BarrierXP® insulating glass package features Low-E glass, argon gas³ and the Intercept® Warm-Edge Spacer System for increased energy savings
- Jamb extensions reduce interior trim for installation ease

INTERIOR GRIDS

Customize your patio door with decorative grids. All grids are enclosed within the insulated glass unit for easy cleaning.

Grid Patterns



Griu Prollies



COLOR COLLECTION

Make a beautiful first impression with our versatile palette of subtle shades and bold architectural hues.

Interior Colors

Beige4

Classic Clay

White⁴
Exterior Colors











Classic Clay4



3773 State Road, Cuyahoga Falls, Ohio 44223 www.gentekinc.com

Make us a part of your home.







'See your Gentek Sales Representative for additional information regarding any questions you might have, or any assertions herein, concerning energy efficiency or savings. Energy savings will vary. ²Available on the 80° door height only. ³Insulated glass (IG) units that require capillary tubes may experience some argon gas depletion. ⁴Extruded solid color. Colors may be slightly different from their appearance in this brochure. Make final color selections using actual product samples. All specifications and designs subject to change without notice. Due to product changes, improvements and other factors, Gentek reserves the right to change or delete information contained herein without prior notice. WRARNING: Screen will not stop child from failing out patio door. Keep child away from open door. The only purpose of the screen is to reduce infiltration of insects. Intercept is a registered trademark of Vitro Architectural Glass. ENERGY STAR name and logo are registered U.S. marks and are owned by the U.S. government. USGBC and related logo is a trademark owned by the U.S. Green Building Council.